





- FADGI AND ISO 19264-1 COMPLIANT
- MAXIMUM SCAN HEIGHT OF 100 MM / 4 INCHES
- DOCUMENT THICKNESS OF 200 MM / 8 INCHES
- FASTEST COLOR SCANNING AT 42.2 MM/S / 1.66 INCH/S @ 300 DPI
- FASTEST 3D TEXTURE COLOR SCANNING AT 21.1 MM/S / 0.83 INCH/S @ 300DPI
- 600 x 600 DPI OPTICAL RESOLUTION
- CAPTURES 3D SURFACES, TEXTURES OF VARIOUS MATERIALS
- CONTACT-FREE SCANNING OF FRAGILE MATERIAL OR EVEN WET ARTWORK
- SCAN2PAD®, USE ANY PAD TO OPERATE THE SCANNER
- SCAN TABLE CAN BE MOVED MANUALLY OR MOTORIZED
- INTEGRATED 64BIT LINUX, INTEL I3 QUAD CORE, 8 GB RAM, 320GB HDD
- GIGABIT TCP/IP NETWORK INTERFACE
- LARGE 15 INCH COLOR TOUCHSCREEN FOR SIMPLIFIED OPERATION
- VIRTUAL RESCAN, MODIFY IMAGES WITHOUT RESCANNING
- LED LAMPS, NO WARM UP, IR/UV FREE
- BUILT TO LAST
- EASY INSTALLATION VIA SCAN2NET® TECHNOLOGY



Enables contact free scanning of works of art like oil and acrylic paintings, watercolors, charcoal and pastel drawings, mixed media collages and antique works of art; at 600dpi in formats up to 914 x 1524mm / 36 x 60 inches.

Using the latest camera technology this scanner exceeds all criteria set forth in the FADGI *** guidelines and ISO 19264-1 level B.

Contact free scanning at 600 dpi

NEW! Large Format Overhead Scanner
Complete ScanStation Solution
Scan to Network, USB, Tablet, Phone or Device
No PC Required! (Apple iOS and Android Compatible)

ScanWide.com

The WideTEK® 36ART-600 enables contact free scanning of works of art like oil and acrylic paintings, watercolors, charcoal and pastel drawings, mixed media collages and antique works of art, with or without frames, gently and in high resolution.

With its patent pending laser focusing, the WideTEK 36ART captures all surface textures, from the finest stroke of the brush to gouache painting techniques. Originals are scanned with up to 600 x 600 dpi optical resolution and ICC profiles can be easily used with the scanner to guarantee truly correct colors in the scanned image.

Contact free scanning allows a maximum height of the scanned surface of up to 100 mm and a complete height of the original of up to 200 mm. A framed work of art can be scanned directly without taking it out of the frame first.

The originals are moved under the CCD camera elements completely contact free, protecting works of art from any damage and making it possible to scan a painting that is still wet, as long as it is framed or the sides are dry enough to place the artwork on the scanning bed. Cool UV and IR-free LED illumination also protects valuable art from color distortion or damage due to excessive exposure to light.

TECHNICAL DATA

Maximum Document Size	914 x 1524 mm (36 x 60 inches)
Maximum Scan Heights	100 mm (4 inch)
Document Thickness	200 mm (8 inch) E.g. Canvas up to max. 100 mm in a frame up to 200 mm thickness
Optical Resolution	600 x 600 dpi
Scan Speed Color	300 dpi - 42.2 mm/s (1.66 inch/s), 600 dpi - 21.1 mm/s (0.83 inch/s)
Scan Speed Color 3D	300 dpi - 21.1 mm/s (0.83 inch/s), 600 dpi - 10.7 mm/s (0.42 inch/s)
Color Depth	48 bit color, 16 bit grayscale
Scan Output	24 bit color, 8 bit color indexed, 8 bit grayscale, bitonal, enhanced halftone
File Formats	Multipage PDF (PDF/A) and TIFF, JPEG, JPEG 2000, PNM, PNG, BMP, TIFF (Raw, G3, G4, LZW, JPEG),
	AutoCAD DWF, JBIG, DjVu, DICOM, PCX, Postscript, EPS, Raw data
Quality	Exceeds FADGI *** guidelines, ISO 19264-1
Camera	3x Tri-Color CCD, 67.500 pixels, encapsulated and dust-proof
Light Source	Two lamps with white LEDs, integrated optical diffusor, no IR/UV radiation
Computer	64 bit Linux, Intel i3, quad core processor, 8 Gigabyte RAM, 320GB HDD for extra large jobs
Touchscreen / Monitor	15 inch color touchscreen
USB Port	1 USB Port 3.0
Interface	1 GBit Fast Ethernet with TCP/IP based Scan2Net® Interface
Dimensions Scanner (H x W x D)	with runway: 1380 x 3275 x 1280 mm (54.3 x 128.9 x 50.4 inches)
	without runway: 1380 x 690 x 1280 mm (54.3 x 27.2 x 50.4 inches)
	Scan table: 1000 x 2100 mm (39.4 x 82.7 inches)
Weight Scanner / scan table	200 kg (440 lbs.) / 22,5 kg (50 lbs.)
Electrical Connection	100 – 240 Vac, 47 – 63 Hz (external power supply, complies with ECO standard CEC level VI)
Power Consumption	<0.5 W (Sleep) / 5.2 W (Standby) / <50 W (Ready to scan) / <110 W (Scanning)
Operating Temperature	5 to 40 °C, 40 to 105 °F
Relative Humidity	20 to 80 % (non-condensing)
Noise	< 35 dB(A) (Scanning) / < 25 dB(A) (Standby)
Approvals	IEC/EN 62368-1: 2013, UL/CSA 62368-1 Ed.2, EN 55022, EN 55024; FCC 47 Part 15





















Visit our homepage!



673 Potomac Station Drive #103 Leesburg, VA 20176

(800) 681-8520 info@scanwide.com